



【Product Feature】

- Two ears wearing, enhance comfort and clarity
- The Ultra noise canceling Mic filters 80% background noise
- Broad Band audio frequency
- Hearing protection with Active Protection™ technology
- DSP audio processing technology
- Inline telephone functions: pick up, mute and volume control
- Ultra Flex™ MIC wires, boom rotation >20k times
- Option to apply for Avaya, Lync UC system
- Optimized for noisy official users and call center users



【Specifications】

1. Features			
➤ Receiving Type	Dynamic moving coil	➤ Connection type	USB
➤ Microphone	ECM	➤ Microphone boom	300° adjustable
➤ Wearing Style	Adjustable headband	➤ Comfort aid	Leather/Foam ear cushion
➤ Communication function	Mute & Volume control	➤ Special function	Built-in sound card
2. Mechanical Specifications			
➤ Weight (with cable)	130g	➤ Contacts	Phosphor bronze gold-plated
➤ Cord length	2.1m, straight	➤ Housing	PA66 Shell Injection
➤ Insertion cycles	10000 minimum	➤ Storage Temperature	- 25℃~65℃
3. Electroacoustical Specifications			
Receiving			
➤ Diameter ϕ	27 mm	➤ THD @ 1kHz	<5%
➤ Rated Frequency Range	Broad Band (150~6.8 kHz)	➤ Max in-band Distortion	<10%
➤ Nominal Impedance	150 Ω ±15%	Sealed acoustic press limit @ 1Khz	Measured according to IEC. 318 Standard Audio Test
➤ Sealed Sensitivity @ 1kHz	100 ± 3dB		
Transmitting			
➤ Rated Frequency Range	100-10KHz	➤ Noise canceling (below 1kHz, far field)	Noise canceling
➤ Directivity	Cardioid	➤ Sensitivity @ 1kHz @ 1kHz (RL=2.2K Ω Vs=3.0V DC 0dB=1V/Pa)	-49 ± 3 dB

VT 2000 USB



VBet Electronics Co.,Ltd
